

BELGARD
PAVES THE WAY

RESOURCE GUIDE | NORTHFIELD EAST | IN, KY, MI, OH, PA

LIFETIME TRANSFERABLE LIMITED WARRANTY

Oldcastle® APG, Inc. ("Belgard") is proud to inform you that all of our interlocking concrete paver and retaining walls ("Products") meet and/or exceed the requirements of ASTM C-936 and ASTM C-1372. Belgard® guarantees its Products against these standards for the lifetime of the Product defined by ICPI. This guarantee does not apply to splitting, chipping or other breakage that could be caused by impact, abrasion or overloading. This warranty is transferable. The original proof of purchase is required.

This warranty is only valid if the material is installed under the guidelines of the ICPI (www.ICPI.org), The NCMA (www.ncma.org) or the Belgard Installation Guideline Manual. Improper installation voids this warranty. This warranty is for residential applications only and does not apply to commercial applications. It is recommended that the job be installed by a Belgard Contractor Program participant who guarantees their workmanship for a minimum of 3 years from the date of install. For warranty service, contact Belgard at 877-BELGARD. A service representative will investigate your claim within 10 business days. If the Belgard product fails to meet the specifications, Belgard will replace the defective product at no charge. Color matching cannot be guaranteed. Belgard will not be responsible for any replacement labor, consequential damages or incidental damages. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Some states do not allow for the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

For specific information regarding warranty coverage and exclusions in regards to the Elements™ and Porcelain Paver products, please visit: Belgard.com/Warranty.

ABOUT US

At Belgard®, we take our role as industry leaders seriously. Our rigorous research and development program is centred on innovation and quality. We never take it for granted that our products are the best in the business and constantly strive to improve and take the industry to the next level. Our overarching goal is to continue to find new and exciting ways to create beautiful outdoor spaces while maintaining incredibly high standards for product quality and performance.

Since 1995, our locally made and nationally backed products have transformed thousands of residential and commercial properties across North America. With more shapes, styles and textures than any other brand, Belgard's Outdoor Living paving and wall products aren't just functional, they infuse outdoor spaces with distinctive atmosphere and style.

Every day, our network of Belgard Authorized Dealers and Contractors helps customers realize their outdoor dreams. And every year, we strive to improve our product and service offerings by dedicating more than 20,000 hours to research and development. By staying ahead of design trends, we are able to provide design-forward products that homeowners envision for their backyard spaces.

All of our outdoor products—when installed by a Belgard Authorized Contractor—are covered by a transferable lifetime limited warranty. That's just part of our commitment to lasting outdoor beauty.

PAVERS & SLABS

PAVERS & SLABS INSTALLATION GUIDE

4 Interlocking Concrete Pavement


PAVERS & SLABS

| | | | |
|----|-------------------|----|-----------|
| 5 | Basalt™ | 29 | Old York™ |
| 7 | Belgian Cobble® | 30 | Origins™ |
| 9 | Brooklyn™ | | |
| 10 | Cambridge Cobble® | | |
| 12 | Dimensions™ | | |
| 16 | Dublin Cobble® | | |
| 20 | Holland Stone | | |
| 22 | Mega-Libre® | | |
| 24 | Geometric Shapes | | |
| 26 | Melville™ Plank | | |


For basic paver installation information
visit icpi.org

INTERLOCKING CONCRETE PAVEMENT (ICP)


PATIO/WALK/RESIDENTIAL DRIVEWAY WITH PLASTIC EDGE RESTRAINT CROSS SECTION




RESIDENTIAL DRIVEWAY WITH CONCRETE EDGES CROSS SECTION



PATIO/SIDEWALK ON COMPACTED AGGREGATE BASE CROSS SECTION



SWIMMING POOL DECK AND COPING CROSS SECTION





Scan for additional
product information

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA | T2 PROCESS |
|------------|-----------------------|---------------|-----------|-----|------------|
| | | | | | |
| ✓ | | | | | ✓ |

SHAPES & SIZES

3-Piece



6 x 12 x 2³/₈



12 x 12 x 2³/₈



18 x 12 x 2³/₈

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | UNITS/ LAYER | UNITS/ SQFT | WEIGHT/ PALLET | LNFT/PALLET (SOLDIER) | LNFT/PALLET (SAILOR) |
|----------------|-----------------|----------------|------------------|------------------|-----------------|----------------|-------------------|--------------------------|-------------------------|
| 3-PIECE | | | | | | | | | |
| 12 | 120 | 12 | 10 | 120 | 12 | – | 3660 | – | 120 |



NOTES:

AutoCAD® hatch pattern files can be downloaded from belgard.com for use in architectural drawings.


Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.

Percentages are based on area by paver.

6 x 12

12 x 12

12 x 18





Scan for additional product information

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA |
|------------|-----------------------|---------------|-----------|-----|
| | | | | |
| ✓ | ✓ | | ✓ | |

SHAPES & SIZES

Multi-Piece



Variable x 2³/₈

| UNIT | SQFT/PALLET | SQFT/LAYER | LAYER/PALLET | UNITS/PALLET | UNITS/LAYER | UNITS/SQFT | WEIGHT/PALLET | LNFT/PALLET (SOLDIER) | LNFT/PALLET (SAILOR) |
|--|-------------|------------|--------------|--------------|-------------|------------|---------------|-----------------------|----------------------|
| MULTI-PIECE | | | | | | | | | |
| VARIABLE X 2³/₈ | 68 | – | – | 320 | – | – | 1640 | – | – |


Lay pavers at random.

NOTES:

AutoCAD® hatch pattern files can be downloaded from belgard.com for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.







Percentages are based on area by paver.





Scan for additional
product information

Pattern found on page 21

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA | T2 PROCESS |
|---|---|---|---|---|---|
|  |  |  |  |  |  |
| ✓ | ✓ | | | | ✓ |

60mm



3 x 9 x 2³/₈

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | UNITS/ LAYER | SQFT/ UNIT | WEIGHT/ PALLET | LNFT/PALLET (SOLDIER) | LNFT/PALLET (SAILOR) |
|---|-----------------|----------------|------------------|------------------|-----------------|---------------|-------------------|--------------------------|-------------------------|
| 60MM | | | | | | | | | |
| 3 X 9 X 2³/₈ | 103.13 | 10.3 | 10 | 550 | 55 | .188 | 2805 | 137.5 | 412.5 |



Scan for additional
product information

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA | TRUECOLOR PROCESS |
|------------|-----------------------|---------------|-----------|-----|-------------------|
| | | | | | |
| ✓ | ✓ | | | | ✓ |


SHAPES & SIZES

Square



6 x 6 x 2³/₈

Rectangle



6 x 9 x 2³/₈

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | UNITS/ LAYER | SQFT/ UNIT | WEIGHT/ PALLET | LNFT/PALLET (SOLDIER) | LNFT/PALLET (SAILOR) |
|------------------|-----------------|----------------|------------------|------------------|-----------------|---------------|-------------------|--------------------------|-------------------------|
| SQUARE | | | | | | | | | |
| SQUARE | 120 | 12 | 10 | 480 | 48 | .25 | 3140 | 240 | 240 |
| RECTANGLE | | | | | | | | | |
| RECTANGLE | 113 | 11.30 | 10 | 300 | 30 | .375 | 3051 | 150 | 225 |

NOTES:

AutoCAD® hatch pattern files can be downloaded from belgard.com for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.


Percentages are based on area by paver.

6 x 6 Squares


6 x 9 Rectangles

Pattern can also used for Brooklyn, found on page 9, Holland Stone, found on page 20 and Old York found on page 29.


2-PIECE MUSTER K PATTERN (25% 6x6 75% 6x9)




2-PIECE RUNNING BOND PATTERN



1-PIECE RUNNING BOND PATTERN










1-PIECE HERRINGBONE PATTERN





Scan for additional
product information

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA | DURAFUSION PROCESS | TRUECOLOR PROCESS |
|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |
| ✓ | ✓* | | | ✓ | ✓ | ✓** |

*Only applicable for Dimensions 6 and accents.

**Only applicable for Dimensions 12.

SHAPES & SIZES

Dimensions 6*



3 x 6 x 2³/₈



6 x 6 x 2³/₈



6 x 9 x 2³/₈

Dimensions 12**



6 x 12 x 2³/₈




12 x 12 x 2³/₈




12 x 18 x 2³/₈


Dimensions 18



9 x 18 x 2³/₈




18 x 18 x 2³/₈




18 x 27 x 2³/₈


Dimensions Slabs



12 x 24 x 2³/₈



24 x 24 x 2³/₈



24 x 36 x 2³/₈

Accent 3 x 9



3 x 9 x 2³/₈

Accent 6 x 9



6 x 9 x 2³/₈

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | UNITS/ LAYER | SQFT/ UNIT | WEIGHT/ PALLET | LNFT/PALLET (SOLDIER) | LNFT/PALLET (SAILOR) |
|------|-----------------|----------------|------------------|------------------|-----------------|---------------|-------------------|--------------------------|-------------------------|
|------|-----------------|----------------|------------------|------------------|-----------------|---------------|-------------------|--------------------------|-------------------------|

DIMENSIONS 6

| | | | | | | | | | |
|---|-----|----|----|-----|----|---|------|---|-----|
| 3 X 6 X 2 ³ / ₈ 6 X 6 X 2 ³ / ₈ 6 X 9 X 2 ³ / ₈ | 120 | 12 | 10 | 480 | 48 | – | 3516 | – | 240 |
|---|-----|----|----|-----|----|---|------|---|-----|

DIMENSIONS 12

| | | | | | | | | | |
|--|-----|----|----|-----|----|---|------|---|-----|
| 6 X 12 X 2 ³ / ₈ 12 X 12 X 2 ³ / ₈ 18 X 12 X 2 ³ / ₈ | 120 | 12 | 10 | 120 | 12 | – | 3516 | – | 120 |
|--|-----|----|----|-----|----|---|------|---|-----|

DIMENSIONS 18

| | | | | | | | | | |
|--|-------|-------|----|----|---|---|------|---|------|
| 9 X 18 X 2 ³ / ₈ 18 X 18 X 2 ³ / ₈ 27 X 18 X 2 ³ / ₈ | 112.5 | 11.25 | 10 | 50 | 5 | – | 3296 | – | 82.5 |
|--|-------|-------|----|----|---|---|------|---|------|

SLABS

| | | | | | | | | | |
|---|-----|----|----|----|---|---|------|----|-----|
| 12 X 24 X 2 ³ / ₈ | 120 | 12 | 10 | 60 | 6 | 2 | 3384 | 60 | 120 |
| 24 X 24 X 2 ³ / ₈ | 80 | 12 | 10 | 20 | 2 | 4 | 2256 | 40 | 40 |
| 24 X 36 X 2 ³ / ₈ | 120 | 12 | 10 | 20 | 2 | 6 | 3516 | 40 | 60 |

ACCENTS

| | | | | | | | | | |
|---------------------------------------|--------|-------|----|-----|----|------|------|-------|-------|
| 3 X 9 X 2 ³ / ₈ | 103.13 | 10.31 | 10 | 550 | 55 | .188 | 2805 | 137.5 | 412.5 |
| 6 X 9 X 2 ³ / ₈ | 112.5 | 11.25 | 10 | 300 | 30 | .375 | 3296 | 150 | 225 |



NOTES:


AutoCAD® hatch pattern files can be downloaded from belgard.com for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.


Percentages are based on area by paver.

Pattern can also be used for Origins 3-Piece, found on page 30.


3-PIECE PATTERN A (Dimensions™ 6 & Dimensions™ 12)



3-PIECE PATTERN B (Dimensions™ 18)



3-PIECE PATTERN A (Dimensions™ 12)



NOTES:

AutoCAD® hatch pattern files can be downloaded from belgard.com for use in architectural drawings.


Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.

Percentages are based on area by paver.

20% 12 x 24

40% 24 x 24

40% 24 x 36





Scan for additional
product information

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA | DURAFUSION PROCESS |
|------------|-----------------------|---------------|-----------|-----|--------------------|
| | | | | | |
| ✓ | ✓ | | | | |

SHAPES & SIZES

3-Piece Modular



3 x 6 x 2³/₈



6 x 6 x 2³/₈




6 x 9 x 2³/₈



6 x 9 x 2³/₈

Accent

Circle Kit



5⁷/₈ x Variable x 2³/₈

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | UNITS/ LAYER | SQFT/ UNIT | WEIGHT/ PALLET | LNFT/PALLET (SOLDIER) | LNFT/PALLET (SAILOR) |
|------|-----------------|----------------|------------------|------------------|-----------------|---------------|-------------------|--------------------------|-------------------------|
|------|-----------------|----------------|------------------|------------------|-----------------|---------------|-------------------|--------------------------|-------------------------|

3-PIECE MODULAR

| | | | | | | | | | |
|------------------|-------|-------|----|-----|----|------|---------|---|--------|
| TWINKIE | 21.35 | 1.94 | – | 176 | 16 | .125 | 577.28 | – | 42.17 |
| SQUARE | 42.63 | 3.88 | – | 176 | 16 | .25 | 1151.04 | – | 85.25 |
| RECTANGLE | 64.02 | 5.85 | – | 176 | 16 | .375 | 1726.56 | – | 128.78 |
| TOTAL | 128 | 11.64 | 11 | 528 | – | – | 3455 | – | 256.18 |

ACCENT

| | | | | | | | | | |
|---------------|-------|-------|----|-----|----|------|------|-----|-----|
| ACCENT | 112.5 | 11.25 | 10 | 300 | 30 | .375 | 2981 | 150 | 225 |
|---------------|-------|-------|----|-----|----|------|------|-----|-----|

CIRCLE KIT

| | | | | | | | | | |
|-------------------|----|-----|----|-----|----|---|------|---|---|
| CIRCLE KIT | 73 | 7.3 | 10 | 420 | 42 | – | 2992 | – | – |
|-------------------|----|-----|----|-----|----|---|------|---|---|

NOTES:

AutoCAD® hatch pattern files can be downloaded from belgard.com for use in architectural drawings.


Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.

6 x 3 Small Rectangle


6 x 6 Medium Square

6 x 9 Large Rectangle

3-PIECE PATTERN A




3-PIECE RUNNING BOND



NOTES:

AutoCAD® hatch pattern files can be downloaded from belgard.com for use in architectural drawings

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.



To get a complete circle, be sure to follow the laying order illustrated at left.

UNIT SIZES



Each pallet contains enough pavers for:

2 circles with diameters 6' 5"

or

1 circle with diameter 9' 5"

Note: For larger circle, combined 2 circle kits to make a circle with diameter of 13'6"

* Each pallet layer contains one Mold Filler Piece A and B. They are not used in the Dublin Circle Layout. Each piece is accounted for in weights mentioned in the table below. Square footage does not account for these pieces. Their purpose is solely for packaging and shipping stability.



Scan for additional product information

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA | DURAFUSION PROCESS | TRUECOLOR PROCESS |
|------------|-----------------------|---------------|-----------|-----|--------------------|-------------------|
| | | | | | | |
| ✓ | ✓ | | | ✓ | ✓* | ✓* |

*Available with either DuraFusion or TrueColor

SHAPES & SIZES

60mm



4 x 8 x 2³/₈

| UNIT | SQFT/PALLET | SQFT/LAYER | LAYER/PALLET | UNITS/PALLET | UNITS/LAYER | SQFT/UNIT | WEIGHT/PALLET | LNFT/PALLET (SOLDIER) | LNFT/PALLET (SAILOR) |
|------|-------------|------------|--------------|--------------|-------------|-----------|---------------|-----------------------|----------------------|
|------|-------------|------------|--------------|--------------|-------------|-----------|---------------|-----------------------|----------------------|

60mm with Truecolor

| | | | | | | | | | |
|---------------------------------------|-----|----|----|-----|----|-------|------|-----|-----|
| 4 X 8 X 2 ³ / ₈ | 120 | 12 | 10 | 540 | 54 | .2222 | 3112 | 180 | 360 |
|---------------------------------------|-----|----|----|-----|----|-------|------|-----|-----|

60mm with Durafusion

| | | | | | | | | | |
|---------------------------------------|-----|----|----|-----|----|-------|------|-----|-----|
| 4 X 8 X 2 ³ / ₈ | 120 | 12 | 10 | 540 | 54 | .2222 | 3516 | 180 | 360 |
|---------------------------------------|-----|----|----|-----|----|-------|------|-----|-----|

NOTES:

AutoCAD® hatch pattern files can be downloaded from belgard.com for use in architectural drawings.


Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.

Percentages are based on area by paver.


100% 4 x 8

Pattern can also be used for Brooklyn found on page 9 and for Old York found on page 29.


1-PIECE RUNNING BOND PATTERN



1-PIECE HERRINGBONE PATTERN








1-PIECE BASKET WEAVE PATTERN





Scan for additional
product information

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA |
|---|---|---|---|---|
|  |  |  |  |  |
| ✓ | | | | |

SHAPES & SIZES

Small Unit



16¼ x 23¾ x 2¾

Large Unit



16¼ x 31 x 2¾

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | UNITS/ LAYER | UNITS/ SQFT | WEIGHT/ PALLET | LNFT/PALLET (SOLDIER) | LNFT/PALLET (SAILOR) |
|--------------|-----------------|----------------|------------------|------------------|-----------------|----------------|-------------------|--------------------------|-------------------------|
| 60mm | | | | | | | | | |
| TOTAL | 86 | 8.60 | 10 | 40 | 4 | – | 2427 | – | – |




NOTES:

AutoCAD® hatch pattern files can be downloaded from belgard.com for use in architectural drawings

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.

23% 15⁵/₆ x 22 Units








77% 15¹/₂ x 29³/₄ Units



GEOMETRIC SHAPES




Scan for additional product information


| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA | DURAFUSION PROCESS | TRUECOLOR PROCESS |
|---|---|---|---|--|---|---|
|  |  |  |  |  |  |  |
| ✓ | | | | ✓ | | ✓ |

SHAPES & SIZES

Hexagon




10⁷/₁₆ x 11⁷/₈ x 2³/₈




Diamond




12 x 12 x 2³/₈




3 x 12 Parallelogram




3 x 12 x 2³/₈



6 x 18 Parallelogram



6 x 18 x 2³/₈









| UNIT | SQFT/PALLET | SQFT/LAYER | LAYER/PALLET | UNITS/PALLET | UNITS/LAYER | SQFT/UNIT | WEIGHT/PALLET | LNFT/PALLET (SOLDIER) | LNFT/PALLET (SAILOR) |
|--|-------------|------------|--------------|--------------|-------------|-----------|---------------|-----------------------|----------------------|
| HEXAGON | | | | | | | | | |
| 10 ⁷ / ₁₆ X 11 ⁷ / ₈ X 2 ³ / ₈ | 100.02 | 8.34 | 12 | 108 | 9 | .861 | 2664 | – | – |
| DIAMOND | | | | | | | | | |
| 12 X 12 X 2 ³ / ₈ | 93.53 | 7.79 | 12 | 108 | 9 | 1 | 2664 | – | – |
| 3 X 12 PARALLELOGRAM | | | | | | | | | |
| 3 X 12 X 2 ³ / ₈ | 85.73 | 7.79 | 11 | 396 | 36 | .25 | 2664 | – | – |
| 6 X 18 PARALLELOGRAM | | | | | | | | | |
| 6 X 18 X 2 ³ / ₈ | 114.31 | 10.39 | 11 | 176 | 16 | .75 | 3165 | – | – |

BELGARD.COM | 877-235-4273

NOTES:

AutoCAD® hatch pattern files can be downloaded from belgard.com for use in architectural drawings.







Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.



MELVILLE™ PLANK



Scan for additional
product information

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA | DURAFUSION PROCESS |
|---|---|---|---|---|---|
|  |  |  |  |  |  |
| ✓ | | | | ✓ | ✓ |

SHAPES & SIZES

3-Piece Slim



5 x 11¹³/₁₆ x 2³/₈



5 x 15³/₄ x 2³/₈



5 x 19¹¹/₁₆ x 2³/₈

3-Piece Large



7¹/₂ x 11¹³/₁₆ x 2³/₈



7¹/₂ x 15³/₄ x 2³/₈



7¹/₂ x 19¹¹/₁₆ x 2³/₈

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | UNITS/ LAYER | SQFT/ UNIT | WEIGHT/ PALLET | LNFT/PALLET (SOLDIER) | LNFT/PALLET (SAILOR) |
|------|-----------------|----------------|------------------|------------------|-----------------|---------------|-------------------|--------------------------|-------------------------|
|------|-----------------|----------------|------------------|------------------|-----------------|---------------|-------------------|--------------------------|-------------------------|

3-PIECE SMALL

| | | | | | | | | | |
|--|---------------|--------------|-----------|------------|-----------|----------|-------------|----------|---------------|
| 5 X 11 ¹³ / ₁₆ X 2 ³ / ₈ | 28.87 | 2.88 | – | 70 | 7 | .41 | – | – | 68.91 |
| 5 X 15 ³ / ₄ X 2 ³ / ₈ | 37.97 | 3.79 | – | 70 | 7 | .547 | – | – | 91.875 |
| 5 X 9 ¹¹ / ₁₆ X 2 ³ / ₈ | 47.69 | 4.77 | – | 70 | 7 | .336 | – | – | 114.84 |
| TOTAL | 114.53 | 11.45 | 10 | 210 | 21 | – | 3356 | – | 275.63 |

3-PIECE LARGE

| | | | | | | | | | |
|--|--------------|--------------|-----------|------------|-----------|----------|-------------|----------|---------------|
| 7 ¹ / ₂ X 11 ¹³ / ₁₆ X 2 ³ / ₈ | 31 | 3.10 | – | 50 | 5 | .615 | – | – | 49.22 |
| 7 ¹ / ₂ X 15 ³ / ₄ X 2 ³ / ₈ | 41 | 4.1 | – | 50 | 5 | .82 | – | – | 65.63 |
| 7 ¹ / ₂ X 9 ¹¹ / ₁₆ X 2 ³ / ₈ | 50 | 5.05 | – | 50 | 5 | .505 | – | – | 82.03 |
| TOTAL | 122.7 | 12.27 | 10 | 150 | 15 | – | 3596 | – | 196.88 |

NOTES:

AutoCAD® hatch pattern files can be downloaded from belgard.com for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.

Percentages are based on area by paver.

5 x 11¹³/₁₆

5 x 15³/₄


5 x 19¹¹/₁₆

7¹/₂ x 11¹³/₁₆


7¹/₂ x 15³/₄

7¹/₂ x 19¹¹/₁₆

3-PIECE 7¹/₂ PATTERN



6-PIECE 7¹/₂ & 5 PATTERN





Scan for additional
product information

Pattern found on page 21

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA | DURAFUSION PROCESS |
|------------|-----------------------|---------------|-----------|-----|--------------------|
| | | | | | |
| ✓ | ✓ | | | | ✓ |

SHAPES & SIZES

60mm










3¹⁵/₁₆ X 7⁷/₈ X 2³/₈

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | UNITS/ LAYER | SQFT/ UNIT | WEIGHT/ PALLET | LNFT/PALLET (SOLDIER) | LNFT/PALLET (SAILOR) |
|---|-----------------|----------------|------------------|------------------|-----------------|---------------|-------------------|--------------------------|-------------------------|
| 60mm | | | | | | | | | |
| 3 ¹⁵ / ₁₆ X 7 ⁷ / ₈ X 2 ³ / ₈ | 116.25 | 11.62 | 10 | 540 | 54 | .2222 | 3342 | 177.3 | 354.6 |



Scan for additional
product information

Pattern can also be used for Dimensions 3-Piece,
found on page 12.

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA | DURAFUSION PROCESS | TRUECOLOR PROCESS |
|---|---|---|---|--|---|---|
|  |  |  |  |  |  |  |
| ✓ | ✓* | | | ✓ | ✓ | ✓** |

*Only applicable for Origins 6 and accents.

**Only applicable for Origins 12

SHAPES & SIZES

Origins 6



3 x 6 x 2³/₈



6 x 6 x 2³/₈




6 x 9 x 2³/₈


Origins 12



6 x 12 x 2³/₈




12 x 12 x 2³/₈




12 x 18 x 2³/₈


Origins 18



9 x 18 x 2³/₈



18 x 18 x 2³/₈



18 x 27 x 2³/₈

Accent



6 x 9 x 2³/₈

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | UNITS/ LAYER | SQFT/ UNIT | WEIGHT/ PALLET | LNFT/PALLET (SOLDIER) | LNFT/PALLET (SAILOR) |
|--|-----------------|----------------|------------------|------------------|-----------------|---------------|-------------------|--------------------------|-------------------------|
| ORIGINS 6 | | | | | | | | | |
| 3 X 6 X 2 ³ / ₈ 6 X 6 X 2 ³ / ₈ 6 X 9 X 2 ³ / ₈ | 120 | 12 | 10 | 480 | 48 | – | 3516 | – | 240 |
| ORIGINS 12 | | | | | | | | | |
| 6 X 12 X 2 ³ / ₈ 12 X 12 X 2 ³ / ₈ 12 X 18 X 2 ³ / ₈ | 120 | 12 | 10 | 120 | 12 | – | 3516 | – | 120 |
| ORIGINS 18 | | | | | | | | | |
| 9 X 18 X 2 ³ / ₈ 18 X 18 X 2 ³ / ₈ 18 X 27 X 2 ³ / ₈ | 112.5 | 11.25 | 10 | 50 | 5 | – | 3075 | – | 225 |
| ACCENT | | | | | | | | | |
| 6 X 9 X 2 ³ / ₈ | 112.5 | 11.25 | 10 | 300 | 30 | .375 | 3296 | 160 | 240 |

PERMEABLE PAVERS

PERMEABLE PAVER INSTALLATION GUIDE

33 Basic PICP Systems

PERMEABLE PAVERS



34 Aqualine™

35 Turfstone™

For basic paver installation information
visit icpi.org

PERMEABLE INTERLOCKING CONCRETE PAVEMENT (PICP)







PICP TYPICAL CROSS SECTION





Scan for additional
product information

Pattern found on page 18

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA | TEXTUREGUARD PROCESS |
|---|---|---|---|---|---|
|  |  |  |  |  |  |
| ✓ | ✓ | ✓ | ✓ | ✓ | |

SHAPES & SIZES

80mm









4½ x 9 x 3⅞

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | UNITS/ LAYER | SQFT/ UNIT | WEIGHT/ PALLET |
|-------------|-----------------|----------------|------------------|------------------|-----------------|---------------|-------------------|
| 80MM | | | | | | | |
| 4½ X 9 X 3⅞ | 90 | 11.25 | 8 | 320 | 40 | .2812 | 3375 |



Scan for additional
product information

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA | TEXTUREGUARD PROCESS |
|---|---|---|---|---|---|
|  |  |  |  |  |  |
| ✓ | ✓ | | ✓ | | |

SHAPES & SIZES

Turfstone Unit



15³/₄ x 23⁵/₈ x 3¹/₈

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | UNITS/ LAYER | SQFT/ UNIT | WEIGHT/ PALLET |
|------|-----------------|----------------|------------------|------------------|-----------------|---------------|-------------------|
|------|-----------------|----------------|------------------|------------------|-----------------|---------------|-------------------|

TURFSTONE UNIT

| | | | | | | | |
|---|-------|------|---|----|---|------|------|
| 15 ³ / ₄ X 23 ⁵ / ₈ X 3 ¹ / ₈ | 103.2 | 12.9 | 8 | 40 | 5 | 2.58 | 2377 |
|---|-------|------|---|----|---|------|------|




NOTES:

AutoCAD® hatch pattern files can be downloaded from belgard.com for use in architectural drawings

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.

100% 15³/₄ x 23⁵/₈ Units



PORCELAIN PAVERS & PLANKS

PORCELAIN INSTALLATION GUIDE

- 38 Porcelain Paver Advantages
- 38 Specialty Tools for Porcelain Pavers Construction
- 39 Cleaning & Maintenance For Porcelain Products
- 39 Porcelain Paver Installation
- 40 Sand Set over Compacted Road Base Installation (Pedestrian Foot Traffic)
- 40 Sand Set over Concrete Overlay Installation (Pedestrian Foot Traffic)
- 41 Gravel Set over Open Graded Aggregate Installation
- 42 Cementitious Adhesive Overlay, Concrete Base Installation (Light Vehicular Traffic)

PORCELAIN PAVERS & PLANKS

- | | | | |
|----|--------|----|--------------|
| 43 | Glocal | 46 | Quarziti 2.0 |
| 44 | Lagoon | 47 | Verona™ |
| 45 | Noon | 48 | Unico Coping |

For basic paver installation information
visit icpi.org

PORCELAIN PAVERS

Belgard Porcelain Pavers are formed by pressing, followed by vitrification: this process involves the total fusion into a single material made from natural raw materials (sand, quartz, feldspars, kaolin, clays and inorganic pigments) which, fired at temperatures above 1226.67° C (2240° F), are transformed into a product with exceptional hardness, ultra-low absorption rate and unmatched mechanical characteristics. Belgard porcelain pavers are eco-compatible and ecolabel-certified. Each unit is 20mm (0.7874") standard thickness or ¾" nominal thickness and is durable enough to withstand use in exterior applications.

PORCELAIN PAVERS ADVANTAGES:

- **Freeze thaw resistant**—They are 100% frost-free and their properties remain unaltered at temperatures ranging from -51.1° to + 60° C (-60° F to +140°F).
- **Color durability**—Color is fused by vitrification, becomes an integral part of the porcelain surface and is not affected by elements.
- **Easy installation**—Perfect fit and for fast installs.
- **Low absorption rate**—Spills, salt and other materials will not seep into pours.
- **Easy to clean**—Household cleaners can be used to wipe down spills and dirt; can even be pressure washed with a low pressure washing device* (see pressure washing warning below).*
- **Stylish**—Matches what homeowners are currently doing inside the home.
- **Durable**—High breakage loads of up to 3,587 lbs (1,627 kg) per foot based on ASTM-C648.
- **Resistant**— High compressive strength and ultra-low absorption rate creates a dense surface that resists mold, moss, dirt and other staining.
- **Skid-resistant**—Structured paver top textures create slip resistant surfaces for safety; perfect for around pools/spas or in wet climates.
- **Modular Design**—Superior accuracy in dimensional sizing and linear sides, the slabs allow for perfectly executed installations with tight and accurate lines.
- **Light weight**—16.8 kg (37 lbs) for the 24"x24" paver permit for easy installation, removal and serviceability and even reusability (Excluding adhered installations).
- Available in colors that have an SRI that qualifies for a LEED certification. The SRI on some units ranges between 60-80. To receive LEED credit, the SRI must be at least 29.
- **Impermeable**— Deicing salt and other deicing materials can be used without concern of damage.

* It is important that all pressure washing of your porcelain pavers be done with a low pressure washer with a maximum of 1600 psi and nothing more powerful. When pressure washing your installation, care should be taken to prevent damage to the grout (adhesive and grout installations) and some re-sanding will be necessary when power washing an installation with sand or polymeric sand joints.

SPECIALTY TOOLS FOR PORCELAIN PAVER CONSTRUCTION:

- Wet cut tile saw equipped with a diamond blade manufactured for wet cutting porcelain. The saw should be designed to safely cut a 24 inch length porcelain paver.
- A paver clamp for easy handling, which can be used to both install and remove pavers.
- The use of gloves is highly recommended while handling and installing porcelain slabs.
- Appropriate notched trowels and grout float tools for cementitious adhesive and grout installation. The appropriate tool selection would be based on the adhesive and grout manufacturer's recommendation
- Pallets of porcelain pavers are manufactured and shipped with a Heavy Duty plastic protective pallet cover and the individual porcelain pavers are packaged in protective cardboard boxes. To prevent damage to your pavers, do not remove the protective cardboard boxes until you are ready to install them.
- Caution: Removing pavers from their protective packaging and handling multiple loose stones together creates the possibility for chipping.

Once the Heavy Duty plastic pallet covers have been removed from the pallet, the unused boxed pavers should be protected from the elements to insure the integrity of the protective cardboard boxes.

CLEANING & MAINTENANCE FOR PORCELAIN PRODUCTS

Post-laying cleaning is obligatory after on site works. Inadequate or late removal of the grouting used on the joints can leave marks difficult to remove and create, on the flooring, a cement film able to absorb all types of dirt, thus giving the impression that it is the material that has become dirty.

It is indispensable to dissolve and remove these residues completely using buffered acids diluted in water (follow the instructions on the packs of the products used), which must then be removed completely and quickly, rinsing the floor with plenty of water to avoid residues or drops on the floor which could damage the tiles.

Allow the product to act on the wet floor, without letting it dry and rubbing it with colorless rags. Next, rinse it thoroughly with water to ensure that the floor is free of detergent residues. If necessary, repeat the operation.

We suggest performing a preliminary wash on a sample surface of a few square meters; if the test is successful, extend clearing over the entire surface. When you have done the above wash, carry out a basic or alkaline wash using degreasing detergents. This is because acid can leave grease on the floor, which could contribute to retaining dirt.


PORCELAIN PAVER INSTALLATION

Each of the following option details will include specific information relative to the selected installation. Base thicknesses vary between different geographical and climatic locations and the contractor will be installing typical base thicknesses for paving installations in their location.


Installing porcelain pavers requires the bedding course sand to be pre-compacted and then struck off with a screed to the required thickness as shown in the detail drawings. The porcelain pavers are not compacted and therefore the sand layer beneath them requires pre-compaction. Do not compact dry sand, but insure the sand has a 5 to 6% moisture content so that it will compact cohesively and allow for a smooth strike off finish.

INSTALLATION INFORMATION THAT MUST BE FOLLOWED :


- Weather, soil type and job conditions should be considered when choosing the best installation method.
- When installing porcelain planks (12 x 48, 8 x 48) always lay the pattern of the 1/3s. These should not be placed next to each other at 50%
- NEVER compact porcelain pavers with a plate compactor. Roller compactor recommended for all compaction with porcelain products
- ALWAYS pre-compact and strike off your sand leveling course before installing your porcelain pavers in sand set installations.
- A proper surface drainage system is required to mitigate standing water. Please consider that Belgard Porcelain Paves are impervious, therefore water must be properly discharged and drained away from the pavement.
- Porcelain pavers should only be wet cut with a tile saw equipped with a wet cut porcelain blade.
- NEVER install porcelain pavers without the required 4mm spacing between them. The porcelain pavers should never be installed with a porcelain to porcelain contact. Plastic 4mm spacers (shown at right) should be used on Sand Set and Permeable installations. The photo on the left illustrates the spacer installed in a perspective to support and space 4 paver corners and the photo on the right illustrates the installed spacer snapped apart (as designed) to form Space T that supports 2 paver corners. This versatility will permit your porcelain pavers to be installed in a stack bond pattern, a running bond patterns as well as a flush installation against another structure.
- For a 100 sf. project, approximately 34 spacers are needed; this allows for overages if needed.



4mm spacers




SAND SET OVER COMPACTED ROAD BASE INSTALLATION (PEDESTRIAN FOOT TRAFFIC)



INSTALLATION NOTES:

- Weather, soil type and job conditions should be considered when choosing the best installation method.
- Follow the detailed drawing above
- Base material is to be over based 6 to 8 inches beyond the edge of the pavement.
- Precompact the sand bedding course and screed to 1-in thickness with smooth surface
- The required edge restraint system is a low profile edge restraint with a vertical height of 1 1/2-in as shown in the drawing.
- Insure that pavement is constructed with a 1 1/2 to 2% slope that it is pitched away from any building.
- Insure the plastic 4mm spacers are installed at all corners of the installed pavers


SAND SET OVER CONCRETE OVERLAY INSTALLATION (PEDESTRIAN FOOT TRAFFIC)



INSTALLATION NOTES:

- Weather, soil type and job conditions should be considered when choosing the best installation method.
- A concrete curb with a full depth and finished height is needed to ensure full containment of the bedding sand and the Belgard Porcelain Pavers.
- Precompact the sand bedding course and screed to 1-in thickness with smooth surface
- Mechanically anchor edge restraint into the concrete base.
- Insure geotextile is installed directly on top of the concrete to contain the bedding sand.
- Insure that pavement is constructed with a 1 1/2 to 2 percent slope and that it is pitched away from any building.
- Insure the plastic 4mm spacers are installed at all corners of the installed pavers.


GRAVEL SET OVER OPEN GRADED AGGREGATE INSTALLATION



INSTALLATION NOTES:

- Weather, soil type and job conditions should be considered when choosing the best installation method. Follow the detail drawing.
- The required edge restraint system for this installation has a vertical height of 2½ inches as shown in the drawing. Follow the edge restraint manufacturer's recommendations for the use of their product in permeable applications regarding geogrid usage and placement to maintain the performance of there edging.
- Ensure that pavement is constructed with a 2% slope and that it is pitched away from any building.
- Ensure the 4mm spacers are installed between all pavers.
- The open-graded aggregate should be clean and free from foreign matter, manufactured from crushed rock and conform to ASTM C33 size No. 57. Do not use recycled aggregates or rounded river gravel.
- Additional Drainage: If the project has fine-grained soils, silts or clays, and contributing water sources such as downspouts or groundwater, it is important to install a perforated pipe underdrain to prevent saturation of the subgrade. Make sure underdrain has an acceptable discharge location.
- When installing porcelain planks (12 x 48 & 8 x 48), always lay the pattern of 1/3's. These should not be placed next to each other at 50%.
- compaction
- Roller Compactor recommended for all compaction with Porcelain products

CEMENTITIOUS ADHESIVE OVERLAY, CONCRETE BASE INSTALLATION (LIGHT VEHICULAR TRAFFIC)




INSTALLATION NOTES:






- Insure that pavement is constructed with a 2% slope and that it is pitched away from any building.
- For Cementitious adhesive and grout installation, refer to the manufacturer’s technical instructions and specifically as they relate to outdoor installations.
- For concrete foundation slabs that are not large enough to require contraction / control joints, a minimum 4mm (1/8" to 3/16") grout joint is acceptable, but for larger concrete foundation slabs that do require contraction / control joints, the joint width should be a 3/8". It is absolutely imperative that all contraction / control joints be located in the joint line of installed porcelain pavers and not beneath a paver.
- Caution: If a Porcelain Paver is installed over a control joint, the paver will reflectively crack along the contraction / control joint beneath it.



Scan for additional
product information



Spacers are recommended for all porcelain paver installations.
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.
Please refer to the MIRAGE install guide for driveway install procedure.

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA |
|---|---|---|---|---|
|  |  |  |  |  |
| ✓ | | | | ✓ |

SHAPES & SIZES

24 x 24




23.54 x 23.54 x 3/4






| UNIT | GROSS WEIGHT/ BOX | PIECES/ BOX | SQ FT/ BOX | BOXES/ PALLET | SQ FT/ PALLET | GROSS WEIGHT/ PALLET |
|----------------------------|-------------------|-------------|-------------|---------------|---------------|----------------------|
| 24 X 24 | | | | | | |
| 23.54 X 23.54 X 3/4 | 76 | 2 | 7.75 | 30 | 232.5 | 2280 |



Scan for additional
product information



Spacers are recommended for all porcelain paver installations.
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.
Please refer to the MIRAGE install guide for driveway install procedure.

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA |
|---|---|---|---|---|
|  |  |  |  |  |
| ✓ | | | | ✓ |

SHAPES & SIZES

24 x 48




23.54 x 47.17 x 3/4






| UNIT | GROSS WEIGHT/ BOX | PIECES/ BOX | SQFT/ BOX | BOXES/ PALLET | SQFT/ PALLET | GROSS WEIGHT/ PALLET |
|----------------------------|-------------------|-------------|-----------|---------------|--------------|----------------------|
| 24 X 48 | | | | | | |
| 23.54 X 47.17 X 3/4 | 74 | 1 | 7.75 | 35 | 271.25 | 2621 |



Scan for additional product information



Spacers are recommended for all porcelain paver installations.
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.
Please refer to the MIRAGE install guide for driveway install procedure.

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA |
|---|---|---|---|---|
|  |  |  |  |  |
| ✓ | | | | ✓ |

SHAPES & SIZES

8 x 48




7.64 x 47.17 x 3/4

12 x 48



11.73 x 47.17 x 3/4

Unico



12.99 x 23.54 x 3/4


| UNIT | GROSS WEIGHT/ BOX | PIECES/ BOX | SQFT/ BOX | BOXES/ PALLET | SQFT/ PALLET | GROSS WEIGHT/ PALLET |
|----------------------------|-------------------|-------------|-----------|---------------|--------------|----------------------|
| 8 X 48 | | | | | | |
| 7.64 X 47.17 X 3/4 | 46 | 2 | 5.06 | 30 | 151.8 | 1380 |
| 12 X 48 | | | | | | |
| 11.73 X 47.17 X 3/4 | 74 | 2 | 7.75 | 36 | 279 | 2664 |

QUARZITI 2.0






PORCELAIN COLLECTION 



Scan for additional product information




Spacers are recommended for all porcelain paver installations.
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.
Please refer to the MIRAGE install guide for driveway install procedure.

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA |
|---|---|---|---|---|
|  |  |  |  |  |
| ✓ | | | | ✓ |

SHAPES & SIZES

24 x 24




23.54 x 23.54 x 3/4

24 x 48



23.54 x 47.17 x 3/4

Unico




12.99 x 23.54 x 3/4

| UNIT | GROSS WEIGHT/ BOX | PIECES/ BOX | SQFT/ BOX | BOXES/ PALLET | SQFT/ PALLET | GROSS WEIGHT/ PALLET |
|----------------------------|-------------------|-------------|-------------|---------------|---------------|----------------------|
| 24 X 24 | | | | | | |
| 23.54 X 23.54 X 3/4 | 76 | 2 | 7.75 | 30 | 232.5 | 2280 |
| 24 X 48 | | | | | | |
| 23.54 X 47.17 X 3/4 | 74 | 1 | 7.75 | 35 | 271.25 | 2621 |






MIRAGE[®]
Porcelain.Design.Sustainability



Scan for additional
product information



Spacers are recommended for all porcelain paver installations.
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.
Please refer to the MIRAGE install guide for driveway install procedure.

| PEDESTRIAN | LIGHT/REGULAR TRAFFIC | HEAVY TRAFFIC | PERMEABLE | ADA |
|---|---|---|---|---|
|  |  |  |  |  |
| ✓ | | | | ✓ |

SHAPES & SIZES

24 x 24



23.54 x 23.54 x 3/4


| UNIT | GROSS WEIGHT/ BOX | PIECES/ BOX | SQFT/ BOX | BOXES/ PALLET | SQFT/ PALLET | GROSS WEIGHT/ PALLET |
|----------------------------|-------------------|-------------|-------------|---------------|--------------|----------------------|
| 24 X 24 | | | | | | |
| 23.54 X 23.54 X 3/4 | 76 | 2 | 7.75 | 30 | 232.5 | 2280 |

UNICO COPING






PORCELAIN COLLECTION 



Scan for additional product information




Spacers are recommended for all porcelain paver installations.
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.
Please refer to the MIRAGE install guide for driveway install procedure.

| RESIDENTIAL | COMMERCIAL | STEPS | CAPS | COPING |
|---|---|---|---|---|
|  |  |  |  |  |
| ✓ | | ✓ | | ✓ |

SHAPES & SIZES

Unico




12.99 x 23.54 x 3/4"

| UNIT | GROSS WEIGHT/ BOX | PIECES/ BOX | LN FT/ BOX | BOXES/ PALLET | PIECES/ PALLET | GROSS WEIGHT/ PALLET |
|-----------------------------|-------------------|-------------|------------|---------------|----------------|----------------------|
| UNICO | | | | | | |
| 12.99 X 23.54 X 3/4" | 52 | 3 | 6 | 40 | 120 | 2080 |

Two installation needs, a single solution. UNICO, size 12.99"x 23.51"x 3/4", is processed on both sides, on one side it has a rounded edge and on the other a square edge.

An extremely versatile special piece, which can be used both as a step and as a special piece for swimming pools, with bullnose edge or straight edge, both colored along the side.



ROUNDED EDGE

STRAIGHT EDGE

WALLS

WALL INSTALLATION GUIDE

- 50 Wall Types
- 52 Before You Begin

WALLS

- 53 Diamond® 9D
- 54 Diamond Pro® Straight, Beveled & Smooth Face
- 56 Diamond Pro Stone Cut®
- 58 Easton Stone™
- 59 Highland Stone®
- 61 Melville™ Wall
- 62 Sterling® Wall
- 63 Ashlar Tandem™
- 63 Lamina Tandem
- 63 Melville Tandem™
- 65 Versa-Lok® Standard
- 66 Wellington Wall®
- 67 Weston Stone 3-Piece & Universal

For basic wall installation information
visit ncma.org



*NCMA Segmental
Retaining Wall
Installation Guide*



*NCMA Segmental
Retaining Walls:
Residential Applications*


SEGMENTAL RETAINING WALL TYPES

Segmental retaining walls typically fall into one of three categories.

GRAVITY RETAINING WALL

The first category — a gravity wall — is a retaining wall that does not use soil reinforcement. A gravity wall has height limitations specific to each product. An advantage of this type of retaining wall is that it requires a smaller work area behind the wall.


A gravity wall relies on the weight and setback of the block to resist the soil forces being exerted on the wall.



GEOSYNTHETIC-REINFORCED RETAINING WALL

The second category is a geosynthetic-reinforced wall, which needs to be designed by a qualified engineer. There are (theoretically) no height limitations with reinforced retaining walls, and they are used in larger applications. It requires more work area behind the structure.

The block of soil is stabilized by introducing reinforcement layers into the soil mass behind the facing units. The larger the stabilized soil mass, the more soil can be retained or held back. The geogrid in the soil extends past the theoretical failure plane and serves to create a large, rectangular mass of block and soil, restraining the retained soil.




ANCHORPLEX® SYSTEM

The third category is the Anchorplex system, which offers a unique, non-conventional solution to problematic wall construction sites. It is a retaining wall built with Anchor™ products and structural backfill specified by ANCHOR Diamond, and backed by engineering support tools developed by Anchor.

Use of the Anchorplex system completely eliminates the need for the construction of a mechanically stabilized earth zone behind the wall facing and requires substantially less excavation than is usually necessary in geosynthetic-reinforced wall construction.

Contact ANCHOR Diamond at 1-877-295-5415 for more information about designing and building with the Anchorplex system.




OTHER SEGMENTAL WALL APPLICATIONS

INDEPENDENT TERRACED WALLS


For each wall to be independent of others, they must be built using a 2:1 ratio: The upper wall must be built a distance away from the lower wall of at least twice the height of the lower wall. In addition, the upper wall must also be equal to or less than the height of the lower wall. Exceptions to this general rule include weak soil conditions or where slopes exist above, below or between wall locations. For example, if the lower terrace is 4 feet tall, the distance between the terraces must be at least 8 feet and the upper wall must not be higher than 4 feet.

Proper drainage is vital to maintaining stable, long-lasting terraced walls. A drainpipe must be installed so that the water is directed around or under the lower wall. Never place the drainpipe outlet for the upper wall above or behind the lower wall.



DEPENDENT TERRACED WALLS

When the distance between the lower and upper walls is less than twice the height of the lower wall, the walls become structurally dependent on each other. In this situation, it is important to take global stability into account, incorporating additional reinforcement — and longer layers — into the wall plan. In addition, structurally dependent walls require even more excavation, backfill and time. So plan ahead and be sure to check the wall plan for specific requirements. For structurally dependent walls, consult with a qualified engineer.



BEFORE YOU BEGIN

Advance planning and careful layout at the job site help ensure a successful retaining and freestanding wall project.









- Review the site plan to confirm lot lines, wall location, length and elevations.
- Understand on-site soils. Ideal soils are sand and gravel. For walls built in clay or poor soils, work with a local engineer to confirm the wall design and the required soil reinforcement. Black or organic soils should not be used as backfill.
- Confirm the location of underground utilities. Call 811.
- Seek all necessary building permits.
- Prepare a drawing of the site with the wall location, lengths and elevations.
- Plan drainage to avoid erosion or buildup of water behind the wall. Consider where the water will drain through the wall, where downspouts will expel and whether there's an underground sprinkler. For walls greater than three feet in height, a perforated drainpipe is recommended at the base of the aggregate to quickly remove large amounts of water.
- A best practice is to divert water away from the wall before it has an opportunity to enter the reinforced soil and gravel fill zone.
- Check the block delivered to ensure it is the correct product and color. Check the geogrids to confirm that it's the strength and weight specified in the engineering plans.
- Be sure to use the right tools. Hand tools include a shovel, 4-foot level, dead-blow hammer, 2- or 3-pound hammer, chisel, hand tamper, hydraulic splitter and string line. Power tools may include a circular saw with a diamond blade and a plate compactor.
- Always wear protective eye wear.

For additional wall installation references go to Belgard.com.






Scan for additional product information

| RESIDENTIAL | COMMERCIAL | STEPS | COLUMNS | FIRE PITS | KITCHEN | FREESTANDING WALL | RETAINING WALL |
|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| ✓ | | ✓ | | | | | ✓ |

SHAPES & SIZES

Block



6 x 17³/₄ x 9

Right Virtual Joint




6 x 17³/₄ x 9

Left Virtual Joint



6 x 17³/₄ x 9

Universal Cap



3 x 18 / 12 x 13

U Start Base Block®



Sold separately. Recommended for use with all available wall block units. Visit Belgard.com for full product information.

3¹/₂ x 18⁷/₁₆ x 12*

*U Start Base Block actual coverage length is 16¹¹/₁₆

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | SQFT/ UNIT | WEIGHT/ UNIT | WEIGHT/ PALLET |
|------|-----------------|----------------|------------------|------------------|---------------|-----------------|-------------------|
|------|-----------------|----------------|------------------|------------------|---------------|-----------------|-------------------|

STRAIGHT FACE

| | | | | | | | |
|--|----|---|---|---------------------------------------|------|----|------|
| 6 X 17 ³ / ₄ X 9 | 45 | 9 | 5 | 30 SOLID 15 LEFT VJ 15 RIGHT VJ | 0.74 | 56 | 3360 |
|--|----|---|---|---------------------------------------|------|----|------|

UNIVERSAL CAP

| | | | | | | | |
|------------------|-------|----------|---|----|---------|-------|------|
| 3 X 18 / 12 X 13 | 90 LF | 11.25 LF | 8 | 72 | 1.25 LF | 54.69 | 3938 |
|------------------|-------|----------|---|----|---------|-------|------|











DIAMOND PRO®

HERITAGE COLLECTION 

METROPOLITAN COLLECTION 




Scan for additional product information

| RESIDENTIAL | COMMERCIAL | STEPS | COLUMNS | FIRE PITS | KITCHEN | FREESTANDING WALL | RETAINING WALL |
|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| ✓ | ✓ | ✓ | ✓ | | | | ✓ |

SHAPES & SIZES

**Special Order*

Diamond Pro Straight Face




8 x 18 x 12

Diamond Pro Beveled Face




8 x 18 x 12

Diamond Pro Corner




8 x 18 x 9

Diamond Pro Cap*



4 x 17¼ / 12 x 10¾

Universal Cap



3 x 18 / 12 x 13

Diamond Pro Smooth Face



8 x 18 x 12

Diamond Pro Smooth Face Corner




8 x 17 x 8

Diamond Pro Smooth Face Cap



4 x 18 / 12 x 12

U Start Base Block®



3½ x 18⁷/₁₆ x 12*

Sold separately. Recommended for use with all available wall block units. Visit Belgard.com for full product information.

**U Start Base Block actual coverage length is 16¹/₁₆.*











| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | SQFT / UNITS | WEIGHT/ UNIT | WEIGHT/ PALLET |
|---------------------------------------|-----------------|----------------|------------------|------------------|-----------------|-----------------|-------------------|
| DIAMOND PRO STRAIGHT FACE | | | | | | | |
| 8 X 18 X 12 | 32 | 8 | 4 | 32 | 1 | 83 | 2653 |
| DIAMOND PRO BEVELED FACE | | | | | | | |
| 8 X 18 X 12 | 32 | 8 | 4 | 32 | 1 | 81 | 2597 |
| DIAMOND PRO CORNER | | | | | | | |
| 8 X 18 X 9 | 32 | 8 | 4 | 32 | 1 | 115 | 3676 |
| DIAMOND PRO CAP | | | | | | | |
| 4 X 17¼ / 12 X 10¾ | 61.02 LF | 10.98 LF | 6 | 54 | 1.22 LF | 53 | 2862 |
| DIAMOND PRO SMOOTH FACE | | | | | | | |
| 8 X 18 X 12 | 36 | 9 | 4 | 36 | 1 | 79 | 2844 |
| DIAMOND PRO SMOOTH FACE CORNER | | | | | | | |
| 8 X 17 X 8 | 22.08 | 11.04 | 2 | 24 | .92 | 82 | 1968 |
| DIAMOND PRO SMOOTH FACE CAP | | | | | | | |
| 4 X 18 / 12 X 12 | 67.5 LF | 11.25 LF | 6 | 54 | 1.25 LF | 57 | 3078 |
| UNIVERSAL CAP | | | | | | | |
| 3 X 18 / 12 X 13 | 90 LF | 11.25 LF | 8 | 72 | 1.25 LF | 55 | 3938 |
| U START BASE BLOCK | | | | | | | |
| 3½ X 18¾ X 12 | 77.84 LF | – | 7 | 56 | 1.39 LF | 51 | 2839 |

DIAMOND PRO STONE CUT®




Scan for additional product information

| RESIDENTIAL | COMMERCIAL | STEPS | COLUMNS | FIRE PITS | KITCHEN | FREESTANDING WALL | RETAINING WALL |
|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| ✓ | ✓ | ✓ | ✓ | | | | ✓ |

SHAPES & SIZES

**Special Order*

Diamond Pro Stone Cut Large Unit




8 x 18 x 12

Diamond Pro Stone Cut Virtual Joint




8 x 18 x 12

Diamond Pro Stone Cut Corner




8 x 18 x 9

Diamond Pro Cap*




4 x 17¼ / 12 x 10¾

Universal Cap



3 x 18 / 12 x 13

U Start Base Block®



3½ x 18⅞ x 12*

Sold separately. Recommended for use with all available wall block units. Visit Belgard.com for full product information.








**U Start Base Block actual coverage length is 16⅞.*



| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | SQFT/ UNIT | WEIGHT/ UNIT | WEIGHT/ PALLET |
|--|-----------------|----------------|------------------|------------------|---------------|-----------------|-------------------|
| DIAMOND PRO STONE CUT LARGE UNIT | | | | | | | |
| 8 X 18 X 12 | 32 | 8 | 4 | 32 | 1 | 87 | 2771 |
| DIAMOND PRO STONE CUT VIRTUAL JOINT | | | | | | | |
| 8 X 18 X 12 | 32 | 8 | 4 | 32 | 1 | 79 | 2515 |
| DIAMOND PRO CORNER | | | | | | | |
| 8 X 18 X 9 | 32 | 8 | 4 | 32 | 1 | 115 | 3676 |
| DIAMOND PRO CAP | | | | | | | |
| 4 X 17¼ / 12 X 10⅝ | 61.02 LF | 10.17 LF | 6 | 54 | 1.22 LF | 53 | 2862 |
| UNIVERSAL CAP | | | | | | | |
| 3 X 18 / 12 X 13 | 90 LF | 11.25 LF | 8 | 72 | 1.25 LF | 55 | 3938 |
| U START BASE BLOCK | | | | | | | |
| 3½ X 18⅞ X 12 | 77.84 LF | – | 7 | 56 | 1.39 LF | 51 | 2839 |




Scan for additional product information

| RESIDENTIAL | COMMERCIAL | STEPS | COLUMNS | FIRE PITS | KITCHEN | FREESTANDING WALL | RETAINING WALL |
|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |


SHAPES & SIZES

Block



4 x 12 x 8

U Start Base Block®



3½ x 18⁷/₁₆ x 12*

Sold separately. Recommended for use with all available wall block units. Visit Belgard.com for full product information.

**U Start Base Block actual coverage length is 16¹¹/₁₆.*

| UNIT | SQFT/PALLET | SQFT/LAYER | LAYER/PALLET | UNITS/PALLET | SQFT/UNITS | WEIGHT/UNIT | WEIGHT/PALLET |
|--|-------------|------------|--------------|--------------|------------|-------------|---------------|
| UNIVERSAL BLOCK - INDIANAPOLIS, IN PLANT | | | | | | | |
| 4 X 12 X 8 | 31.68 | 7.92 | 4 | 96 | .33 | 30.14 | 2893 |
| UNIVERSAL BLOCK - SHEFFIELD VILLAGE, OH PLANT | | | | | | | |
| 4 X 12 X 8 | 39.6 | 6.6 | 6 | 120 | .33 | 29.39 | 3527 |
| U START BASE BLOCK | | | | | | | |
| 3½ X 18 ⁷ / ₁₆ X 12 | 77.84 LF | – | 7 | 56 | 1.39 LF | 51 | 2839 |



Scan for additional product information

| RESIDENTIAL | COMMERCIAL | STEPS | COLUMNS | FIRE PITS | KITCHEN | FREESTANDING WALL | RETAINING WALL |
|-------------|------------|-------|---------|-----------|---------|-------------------|----------------|
| | | | | | | | |
| ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

SHAPES & SIZES

Freestanding Wall



6 x 6 / 4 x 9



6 x 12 / 10 x 9



6 x 18 / 16 x 9



6 x 6 x 12



6 x 12 x 12



6 x 18 x 12

Column/Corner




6 x 18 x 9

Universal Cap



3 x 18 / 12 x 13

U Start Base Block®



3½ x 18¾ x 12*

Sold separately. Recommended for use with all available wall block units. Visit Belgard.com for full product information.

**U Start Base Block actual coverage length is 16 11/16.*



| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | SQFT/ UNIT | WEIGHT/ UNIT | WEIGHT/ PALLET |
|------|-----------------|----------------|------------------|------------------|---------------|-----------------|-------------------|
|------|-----------------|----------------|------------------|------------------|---------------|-----------------|-------------------|

RETAINING WALL

| | | | | | | | |
|-------------|----|---|---|----|------|----|------|
| 6 X 6 X 12 | 8 | 2 | 4 | 32 | 0.25 | 31 | 2912 |
| 6 X 12 X 12 | 16 | 4 | | 32 | 0.50 | 60 | |
| 6 X 18 X 12 | 24 | 6 | 4 | 32 | 0.75 | 81 | 2598 |

FREESTANDING WALL

| | | | | | | | |
|-----------------|------|-----|---|----|------|----|------|
| 6 X 6 / 4 X 9 | 8.4 | 2.1 | 4 | 40 | 0.21 | 26 | 3280 |
| 6 X 12 / 10 X 9 | 18.4 | 4.6 | | 40 | 0.46 | 56 | |
| 6 X 18 / 16 X 9 | 28.4 | 7.1 | 4 | 40 | 0.71 | 87 | 3480 |

UNIVERSAL CAP

| | | | | | | | |
|------------------|-------|----------|---|----|---------|-------|------|
| 3 X 18 / 12 X 13 | 90 LF | 11.25 LF | 8 | 72 | 1.25 LF | 54.69 | 3938 |
|------------------|-------|----------|---|----|---------|-------|------|

U START BASE BLOCK



| | | | | | | | |
|---------------|----------|---|---|----|---------|----|------|
| 3½ X 18⅞ X 12 | 77.84 LF | – | 7 | 56 | 1.39 LF | 51 | 2839 |
|---------------|----------|---|---|----|---------|----|------|

MELVILLE™ WALL

METROPOLITAN
COLLECTION 



Scan for additional
product information

| RESIDENTIAL | COMMERCIAL | STEPS | COLUMNS | FIRE PITS | KITCHEN | FREESTANDING WALL | RETAINING WALL |
|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |


SHAPES & SIZES

Wall Block

Cap



4 x 20 x 10



2 x 20 x 13

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | SQFT/ UNIT | WEIGHT/ UNIT | WEIGHT/ PALLET |
|------|-----------------|----------------|------------------|------------------|---------------|-----------------|-------------------|
|------|-----------------|----------------|------------------|------------------|---------------|-----------------|-------------------|

WALL BLOCK

| | | | | | | | |
|-------------|-------|------|---|----|------|-------|------|
| 4 X 20 X 10 | 26.67 | 4.44 | 6 | 48 | .555 | 61.39 | 2947 |
|-------------|-------|------|---|----|------|-------|------|









CAP

| | | | | | | | |
|-------------|--------|-------|----|----|----------|-------|------|
| 2 X 20 X 13 | 100 LF | 10 LF | 10 | 60 | 1.667 LF | 40.83 | 2450 |
|-------------|--------|-------|----|----|----------|-------|------|





Scan for additional product information

| RESIDENTIAL | COMMERCIAL | STEPS | COLUMNS | FIRE PITS | KITCHEN | FREESTANDING WALL | RETAINING WALL |
|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

SHAPES & SIZES

FSW/SRW/Column Wall Block



6 x 17³/₄ x 12


Anchor™ Fiberglass Pins*



*1 box of pins recommended per pallet, pins sold separately.

0.5 x 5

Universal Cap



3 x 18 / 12 x 13

U Start Base Block®



3¹/₂ x 18⁷/₁₆ x 12*

Sold separately. Recommended for use with all available wall block units. Visit Belgard.com for full product information.

*U Start Base Block actual coverage length is 16¹¹/₁₆.

| UNIT | SQFT/PALLET | SQFT/LAYER | LAYER/PALLET | UNITS/PALLET | SQFT/UNIT | WEIGHT/UNIT | WEIGHT/PALLET |
|------|-------------|------------|--------------|--------------|-----------|-------------|---------------|
|------|-------------|------------|--------------|--------------|-----------|-------------|---------------|

WALL BLOCK


| | | | | | | | |
|---|------|------|---|----|-----|------|------|
| 6 X 17 ³ / ₄ X 12 | 33.3 | 6.66 | 5 | 45 | .74 | 88.5 | 3983 |
|---|------|------|---|----|-----|------|------|

UNIVERSAL CAP

| | | | | | | | |
|----------------|-------|----------|---|----|---------|-------|------|
| 3 X 18/12 X 13 | 90 LF | 11.25 LF | 8 | 72 | 1.25 LF | 54.69 | 3938 |
|----------------|-------|----------|---|----|---------|-------|------|

U START BASE BLOCK

| | | | | | | | |
|--|----------|---|---|----|---------|-------|------|
| 3 ¹ / ₂ X 18 ⁷ / ₁₆ X 12 | 77.84 LF | – | 7 | 56 | 1.39 LF | 50.69 | 2839 |
|--|----------|---|---|----|---------|-------|------|




TANDEM® WALL

FREESTANDING / RETAINING WALLS

NATURAL COLLECTION 
 METROPOLITAN COLLECTION 



Scan for additional product information


| RESIDENTIAL | COMMERCIAL | STEPS | COLUMNS | FIRE PITS | KITCHEN | FREESTANDING WALL | RETAINING WALL |
|---|---|---|---|---|--|---|---|
|  |  |  |  |  |  |  |  |
| ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

SHAPES & SIZES


Ashlar Tandem™



Lamina Tandem™



Melville Tandem™



Tandem Column



Tandem Unit
7 x 18 7/16 x 2 5/8

Column Grid
Height 42

Connector

Items are sold separately. Veneers (1 pallet of Veneers = 2 Columns); Column Grid & Connectors (1 bag of connectors per column grid)

Modular Grid Kit



Modular Grid 42 x 28 3/8
 Connector Panel Connectors & Screws
 Kit includes: 25 Connectors, 15 Stainless Panel Connectors & 15 Stainless Steel Screws.

Tandem Cap Unit




15 x 24 x 3 1/4

8" Connecting Member



3 x 12/8 x 12
 8" connectors are sold separately

Tandem Modular Block® with Universal Connector



7 1/16 x 7 7/8 x 7 7/8

Connectors included. One connector per Modular Block unit.

U Start Base Block®



3 1/2 x 18 1/2 x 12*

*Recommended for use with all available wall block units. (Sold Separately)
 NOTE: U Start Base Block actual coverage length is 16 1/16.

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | SQFT/ UNIT | WEIGHT/ UNIT | WEIGHT/ PALLET |
|------|-----------------|----------------|------------------|------------------|---------------|-----------------|-------------------|
|------|-----------------|----------------|------------------|------------------|---------------|-----------------|-------------------|

ASHLAR TANDEM WALL UNITS

| | | | | | | | |
|--|-------------|--------------|----------|-----------|-------------|----------|-------------|
| 7 X 13 ³ / ₁₆ X 2 ⁵ / ₈ | 19.2 | 3.2 | – | 30 | .64 | 19 | 570 |
| 7 X 15 ¹³ / ₁₆ X 2 ⁵ / ₈ | 23.1 | 3.85 | – | 30 | .77 | 23.2 | 696 |
| 7 X 18 ⁷ / ₁₆ X 2 ⁵ / ₈ | 27 | 4.5 | – | 30 | .9 | 27.2 | 816 |
| TOTAL | 70.1 | 11.69 | 6 | 90 | 2.31 | – | 2082 |

MELVILLE TANDEM WALL UNITS

| | | | | | | | |
|--|-------------|--------------|----------|-----------|-------------|----------|-------------|
| 7 X 13 ³ / ₁₆ X 2 ⁵ / ₈ | 19.2 | 3.2 | – | 30 | .64 | 19 | 570 |
| 7 X 15 ¹³ / ₁₆ X 2 ⁵ / ₈ | 23.1 | 3.85 | – | 30 | .77 | 23.2 | 696 |
| 7 X 18 ⁷ / ₁₆ X 2 ⁵ / ₈ | 27 | 4.5 | – | 30 | .90 | 27.2 | 816 |
| TOTAL | 70.1 | 11.69 | 6 | 90 | 2.31 | – | 2082 |

LAMINA TANDEM WALL UNITS

| | | | | | | | |
|--|--------------|-------------|----------|-----------|----------|----------|-------------|
| 7 X 13 ¹³ / ₁₆ X 2 ⁵ / ₈ | 15.576 | 2.596 | – | 24 | .649 | 19.27 | 462.48 |
| 7 X 15 ⁷ / ₁₆ X 2 ⁵ / ₈ | 18.696 | 3.116 | – | 24 | .779 | 23.13 | 555.12 |
| 7 X 18 ¹ / ₁₆ X 2 ⁵ / ₈ | 21.816 | 3.636 | – | 24 | .909 | 27 | 648 |
| TOTAL | 56.08 | 9.35 | 6 | 72 | – | – | 1666 |

TANDEM CAP UNIT

| | | | | | | | |
|---|----------------|-----|---|----|-----------------|-------|------|
| 15 X 24 X 3 ¹ / ₄ | 20 SF 64 LF | 2.5 | 8 | 32 | .625 SF 2 LF | 93.44 | 2990 |
|---|----------------|-----|---|----|-----------------|-------|------|

COLUMN UNIT

| | | | | | | | |
|--|-------|---|---|----|-----------------------|----|------|
| 7 X 18 ¹ / ₂ X 2 ⁵ / ₈ | 45.43 | 9 | 5 | 50 | 2 COLUMNS/ PALLETS | 27 | 1350 |
|--|-------|---|---|----|-----------------------|----|------|

TANDEM MODULAR BLOCK

| | | | | | | | |
|--|-------|-------|---|-----|-------|----|------|
| 7 ⁷ / ₁₆ X 7 ⁷ / ₈ X 7 ⁷ / ₈ | 49.29 | 12.32 | 4 | 128 | 0.389 | 22 | 2816 |
|--|-------|-------|---|-----|-------|----|------|

U START BASE BLOCK

| | | | | | | | |
|---|----------|---|---|----|---------|----|------|
| 3 ¹ / ₂ X 18 ¹ / ₂ X 12 | 77.84 LF | – | 7 | 56 | 1.39 LF | 51 | 2839 |
|---|----------|---|---|----|---------|----|------|

VERSA-LOK® STANDARD



Scan for additional product information

| RESIDENTIAL | COMMERCIAL | STEPS | COLUMNS | FIRE PITS | KITCHEN | FREESTANDING WALL | RETAINING WALL |
|-------------|------------|-------|---------|-----------|---------|-------------------|----------------|
| | | | | | | | |
| ✓ | ✓ | ✓ | ✓ | ✓ | | ✓ | ✓ |

SHAPES & SIZES







| Standard | Versa-lok C Cap* | Universal Cap | Versa-Pin** |
|----------------|---|------------------|------------------------|
| | | | |
| 6 x 16/14 x 12 | 3 ⁵ / ₈ x 15 ⁵ / ₈ x 11 ⁵ / ₈ | 3 x 18 / 12 x 13 | 2 Versa-Pins Per Block |

*C Cap is only manufactured in Sheffield Village, Ohio. **Sold separately






| UNIT | SQFT/PALLET | SQFT/LAYER | LAYER/PALLET | UNITS/PALLET | SQFT/UNITS | WEIGHT/UNIT | WEIGHT/PALLET |
|---|-------------|------------|--------------|--------------|------------|-------------|---------------|
| VERSA-LOK | | | | | | | |
| 6 X 16/14 X 12 | 24 | 6 | 4 | 36 | .667 | 84.07 | 3027 |
| VERSA-LOK C CAP | | | | | | | |
| 3 ⁵ / ₈ X 15 ⁵ / ₈ X 11 ⁵ / ₈ | 83.79 LF | 11.97 LF | 7 | 63 | 1.33 LF | 47.93 | 3020 |
| UNIVERSAL CAP | | | | | | | |
| 3 X 18/12 X 13 | 90 LF | 11.25 LF | 8 | 72 | 1.25 LF | 54.69 | 3938 |



Scan for additional product information

| RESIDENTIAL | COMMERCIAL | STEPS | COLUMNS | FIRE PITS | KITCHEN | FREESTANDING WALL | RETAINING WALL |
|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

SHAPES & SIZES

| Small | Medium | Large | Universal Cap | Corner Unit |
|---|---|---|--|---|
|  |  |  |  |  |
| 6 x 9 / 6 x 10 | 6 x 12 / 6 x 10 | 6 x 18 / 15 x 10 | 3 x 18 / 12 x 13 | 6 x 12 x 10 |

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | SQFT/ UNITS | WEIGHT/ UNIT | WEIGHT/ PALLET |
|------|-----------------|----------------|------------------|------------------|----------------|-----------------|-------------------|
|------|-----------------|----------------|------------------|------------------|----------------|-----------------|-------------------|

WELLINGTON WALL

| | | | | | | | |
|----------------|------------------|-----|---|----|-------|-------|------|
| 6 X 9/6 X 10 | 6 | 1.5 | – | 16 | .375 | 37.88 | 606 |
| 6 X 12/6 X 10 | 8 | 2 | – | 16 | .50 | 50.5 | 808 |
| 6 X 18/15 X 10 | 12 | 3 | – | 16 | .75 | 75.75 | 1212 |
| TOTAL | 26 SRW 23 FSW | 6.5 | 4 | 48 | 1.625 | – | 2626 |

UNIVERSAL CAP









| | | | | | | | |
|----------------|-------|----------|---|----|---------|-------|------|
| 3 X 18/12 X 13 | 90 LF | 11.25 LF | 8 | 72 | 1.25 LF | 54.69 | 3938 |
|----------------|-------|----------|---|----|---------|-------|------|

CORNER UNIT

| | | | | | | | |
|-------------|----|---|---|----|----|----|------|
| 6 X 12 X 10 | 16 | 8 | 2 | 32 | .5 | 59 | 1888 |
|-------------|----|---|---|----|----|----|------|



Scan for additional product information

| RESIDENTIAL | COMMERCIAL | STEPS | COLUMNS | FIRE PITS | KITCHEN | FREESTANDING WALL | RETAINING WALL |
|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

SHAPES & SIZES


3-Piece



4 x 8 / 5 x 8



4 x 12 / 9 x 8



4 x 16 / 13 x 8

Universal



4 x 12 x 8

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | SQFT/ UNITS | WEIGHT/ UNIT | WEIGHT/ PALLET |
|------|-----------------|----------------|------------------|------------------|----------------|-----------------|-------------------|
|------|-----------------|----------------|------------------|------------------|----------------|-----------------|-------------------|

3-PIECE MODULAR

| | | | | | | | |
|-----------------|-------|------|---|-----|-----|-------|---------|
| 4 X 8 / 5 X 8 | 9.24 | 1.32 | – | 42 | .22 | 16.91 | 710.22 |
| 4 X 12 / 9 X 8 | 13.86 | 1.98 | – | 42 | .33 | 26.23 | 1101.66 |
| 4 X 16 / 13 X 8 | 18.48 | 2.64 | – | 42 | .44 | 36.41 | 1529.22 |
| TOTAL | 42 | – | 7 | 126 | .99 | – | 3341 |

UNIVERSAL


| | | | | | | | |
|------------|----|------|---|-----|------|-------|------|
| 4 X 12 X 8 | 40 | 6.67 | 6 | 120 | .333 | 30.14 | 3617 |
|------------|----|------|---|-----|------|-------|------|

WESTON STONE™ INSTALLATION INSTRUCTIONS


This is a pinless system. Maximum wall height is 2½ feet. Walls exceeding 2½ feet in height may require geogrid reinforcing and the consultation of a qualified engineer. Contact your Belgard sales representative or dealer for assistance.

Weston Stone wall units must be glued with a quality construction adhesive to develop the necessary mechanical bond. All measurements herein are approximate. Natural materials are used in the manufacturing of this product.


WESTON STONE™ WALL PATTERNS



TYPICAL CROSS SECTION WITH WESTON STONE SEAT WALL



TREE RINGS WITH WESTON STONE



FIRE FEATURES

FIRE FEATURES INSTALLATION GUIDE

70 Installation Instructions

FIRE FEATURES

71 Melville™ Series

74 Beaufort™ Series

77 Bordeaux™ Series

80 Brighton™ Series

82 Bristol™ Series

85 Weston Stone Fire Pit Kit

STANDARD INSTALLATION INSTRUCTIONS

GRAVEL BASE

Gravel Fill shall be a clean angular stone or angular granular fill meeting the following gradation as determined in accordance with ASTM D 422.

| <u>Sieve Size</u> | <u>Percent Passing</u> |
|-------------------|------------------------|
| 1-in | 100 |
| 3/4-in | 75-100 |
| No. 4 | 0-60 |
| No. 40 | 0-50 |
| No. 200 | 0-12 |

FOUNDATION PREPARATION

Following excavation of the leveling pad, foundation soil shall be examined to assure the actual foundation soil strength meets or exceeds the assumed design bearing strength. Soils not meeting the required strength shall be removed and replaced with soil meeting the design criteria.



*Scan for Fortified Installation Method
to be used with soft soils or expanding clays*

LEVELING PAD PREPARATION

A minimum 18-in thick layer of compacted granular material shall be placed for use as a leveling pad up to the grades and locations as shown on the construction drawings. The granular base shall be compacted to a firm, level bearing pad on which to place the bottom level of the unit. A leveling pad consisting of 6-in (minimum) thick lean, unreinforced concrete may be used at the contractor's option, or if so detailed on the plans. The leveling pad should extend a minimum of 6-in from the toe and from the heel of the unit base.

GRAVEL FILL

Gravel fill shall be placed to the minimum finished thickness and width shown on the construction plans.

Gravel lifts shall be a maximum thickness of 6-in.

Lifts shall be compacted by three passes of a light weight vibratory plate compactor.

For areas not affected by freeze-thaw conditions please contact your local Belgard sales representative for further installation information.

MELVILLE™ SERIES


METROPOLITAN
COLLECTION 



*Scan for additional
product information*





MELVILLE™ SERIES



FIREPLACE

Rough Dimensions:
2' 7" D x 4' 3" W x 7' 8" H


Approximate Weight:
4205 lbs.



WOOD BOXES

Rough Dimensions:
2' 1" D x 3' 3" W x 3' 1" H


Approximate Weight:
3070 lbs. or 1535 lbs. each




GRILL ISLAND

Rough Dimensions:
2' 8" D x 5' 11" W x 3' 5" H

Approximate Weight:
3500 lbs.



MELVILLE™ SERIES



LINEAR FIRE TABLE


Rough Dimensions:
2' 6" D x 5' 8" W x 2' 5" H

Approximate Weight:
2500 lbs.

LINEAR FIREPLACE

Rough Dimensions:
2' 6" D x 7' 1" W x 5' 4" H

Approximate Weight:
4000 lbs.



FIREPLACE

13070020
Melville Wood Fireplace
Colors: Scandina Gray/Midnight

WOOD BOXES

13140010
Melville Wood Boxes (Pair)
Colors: Scandina Gray/Midnight

36" wood burning fireplace can be converted to a vented gas unit on-site.

GRILL ISLAND

Melville Grill Island (NG)
Colors: Scandina Gray/Midnight

Melville Grill Island (LP)
Colors: Scandina Gray/Midnight

LINEAR FIREPLACE

13000026
Melville Linear Fireplace
Colors: Scandina Gray/Midnight

LINEAR FIRE TABLE


13000027
Melville Linear Fire Table
Colors: Scandina Gray/Midnight

BEAUFORT™ SERIES


NATURAL
COLLECTION 



Scan for additional
product information





BEAUFORT™ SERIES



FIREPLACE

Rough Dimensions:
2' 7" D x 4' 3" W x 7' 8" H


Approximate Weight:
4170 lbs.



WOOD BOXES

Rough Dimensions:
2' 1" D x 3' 3" W x 3' 1" H


Approximate Weight:
3070 lbs.




GRILL ISLAND

Rough Dimensions:
2' 8" D x 6' W x 3' 5" H

Approximate Weight:
3140 lbs.



BEAUFORT™ SERIES



LINEAR FIRE TABLE


Rough Dimensions:
2' 6" D x 5' 8" W x 2' 5" H

Approximate Weight:
2500 lbs.

LINEAR FIREPLACE

Rough Dimensions:
2' 6" D x 7' 1" W x 5' 4" H

Approximate Weight:
3700 lbs.



FIREPLACE

13070010
Beaufort Wood Fireplace
Colors: Shelby/Midnight

WOOD BOXES

13140505
Beaufort Wood Boxes (Pair)
Colors: Shelby/Midnight

36" wood burning fireplace can be converted to a vented gas unit on-site.

GRILL ISLAND

13110518
Beaufort Grill Island (NG)
Colors: Shelby/Midnight

13110818
Beaufort Grill Island (LP)
Colors: Shelby/Midnight

LINEAR FIREPLACE

13000018
Beaufort Linear Fireplace
Colors: Shelby/Midnight

LINEAR FIRE TABLE

13000205
Beaufort Linear Fireplace
Colors: Shelby/Midnight

BORDEAUX™ SERIES


NATURAL
COLLECTION 



Scan for additional
product information





BORDEAUX™ SERIES



FIREPLACE

Rough Dimensions:
2' 7" D x 4' 3" W x 7' 8" H


Approximate Weight:
4200 lbs.



WOOD BOXES

Rough Dimensions:
2' 1" D x 3' 5" W x 3' 1" H


Approximate Weight:
3070 lbs.




GRILL ISLAND

Rough Dimensions:
2' 8" D x 6' W x 3' 5" H

Approximate Weight:
2500 lbs.



BORDEAUX™ SERIES




LINEAR FIRE TABLE

Rough Dimensions:
2' 10³/₄" D x 6' 2" W x 2' 4³/₄" H
Approximate Weight:
2500 lbs.



LINEAR FIREPLACE

Rough Dimensions:
2' 6" D x 7' 1" W x 5' 4" H
Approximate Weight:
3700 lbs.



FIREPLACE

70300791

Bordeaux Wood Fireplace
Colors: Lamina Sienna/Cordova
Stone Buff Base + Top

13070014

Bordeaux Wood Fireplace
Colors: Lamina Sienna/Cordova
Midnight Base + Top

13070012

Bordeaux Wood Fireplace
Colors: Lamina Pewter
Midnight Base + Top

WOOD BOXES

13140001

Bordeaux Wood Boxes (Pair)
Colors: Lamina Sienna/
Cordova Stone Buff

13140020

Bordeaux Wood Boxes (Pair)
Colors: Lamina Sienna/
Cordova Stone Midnight

13140021

Bordeaux Wood Boxes (Pair)
Colors: Lamina Pewter
Midnight Base + Top

GRILL ISLAND

13110010

Bordeaux Grill Island (NG)
Colors: Lamina Sienna/
Cordova Stone Buff
+ Stainless

13110011

Bordeaux Grill Island (LP)
Colors: Lamina Sienna/
Cordova Stone Buff
+ Stainless

13110014

Bordeaux Grill Island (NG)
Colors: Lamina Sienna/
Cordova Stone Midnight
+ Stainless

13110015

Bordeaux Grill Island (LP)
Colors: Lamina Sienna/
Cordova Stone Midnight
+ Stainless

Bordeaux Grill Island (NG)
Colors: Pewter/Midnight
+ Stainless

Bordeaux Grill Island (LP)
Colors: Pewter/Midnight
+ Stainless

LINEAR FIREPLACE

13000021

Bordeaux Linear Fireplace
Colors: Sienna/Buf

13000019

Bordeaux Linear Fireplace
Colors: Sienna/Midnight

13000020

Bordeaux Linear Fireplace
Colors: Pewter/Midnight

LINEAR FIRE TABLE

13000023

Bordeaux Linear Fire Table
Colors: Sienna/Buf

13000204

Bordeaux Linear Fire Table
Colors: Sienna/Midnight

13000203

Bordeaux Linear Fire Table
Colors: Pewter/Midnight


36" wood burning fireplace can be converted to a vented gas unit on-site.

BRIGHTON™ SERIES

HERITAGE
COLLECTION **H**



*Scan for additional
product information*



BRIGHTON™ SERIES

FIREPLACE

Rough Dimensions:
3' 4" D x 4' 4" W x 8' 4" H

Approximate Weight:
5825 lbs.

FIREPLACE

70580007

Brighton Fireplace


Colors: Weston Gascony Tan/Urbana
Ashbury Haze Base + Top

70580378

Brighton Fireplace

Colors: Weston Cotswold Mist/Urbana
Brookstone Slate Base + Top

36" wood burning fireplace can be converted to a vented gas unit on-site.



WOOD BOXES

Rough Dimensions:
2' 4" D x 3' W x 2' 11" H

Approximate Weight:
3200 lbs.

WOOD BOXES

70300046



Brighton Wood Boxes (Pair)

Colors: Weston Gascony Tan/Urbana
Ashbury Haze

70580291

Brighton Wood Boxes (Pair)

Colors: Weston Cotswold Mist/Urbana
Brookstone Slate



BRISTOL™ SERIES

NATURAL
COLLECTION



Scan for additional
product information




BRISTOL™ SERIES

FIREPLACE

Rough Dimensions:
3' D x 5' W x 9' 6" H

Approximate Weight:
5825 lbs.



FIREPLACE

70580261

Colors: Weston Gascony Tan/
Arbel Ashbury Haze Base + Top

70580312

Colors: Weston Cotswold Mist/
Arbel Brookstone Slate Base + Top

36" wood burning fireplace can be
converted to a vented gas unit on-site.

WOOD BOXES

Rough Dimensions:
2' 4" D x 3' W x 3' 3" H

Approximate Weight:
3950 lbs.


WOOD BOXES (PAIR)

70580334

Colors: Weston Gascony Tan/
Urbana Ashbury Haze

70580534

Colors: Weston Cotswold
Mist/Urbana
Brookstone Slate



HEARTH

Rough Dimensions:
2' D x 5' W x 11" H

Approximate Weight:
1180 lbs.



ARCHED HEARTH

70580262




Colors: Weston Gascony Tan/
Arbel Ashbury Haze

70580309

Colors: Weston Cotswold Mist/
Arbel Brookstone Slate



BRISTOL™ SERIES



GRILL ISLAND

Rough Dimensions:
3' D x 6' 8" W x 4' 4" H

Approximate Weight:
3980 lbs.

GRILL ISLAND

13110008

Bristol Grill Island (NG)

Colors: Weston Gascony Tan/
Arbel Ashbury Haze + Stainless

11130250

Bristol Grill Island (LP)

Colors: Weston Gascony Tan/
Arbel Ashbury Haze + Stainless

13110009


Bristol Grill Island (NG)

Colors: Weston Cotswold Mist/
Arbel Brookstone Slate









13110256

Bristol Grill Island (LP)

Colors: Weston Cotswold Mist/
Arbel Brookstone Slate



WESTON STONE™ FIRE PIT KIT

| RESIDENTIAL | COMMERCIAL | STEPS | COLUMNS | FIRE PITS | KITCHEN | FREESTANDING WALL | RETAINING WALL |
|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| ✓ | | | | ✓ | | | |

SHAPES & SIZES

Fire Pit Kit



4 x 8 x 8



4 x 12 x 8

Fire Ring



Outside is 55" in diameter
 Inside is 39.5" in diameter
 Stacks up to 4 rows high
 Metal ring insert included in kit

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | UNITS/ SQFT | WEIGHT/ UNIT | WEIGHT/ PALLET |
|------|-----------------|----------------|------------------|------------------|----------------|-----------------|-------------------|
|------|-----------------|----------------|------------------|------------------|----------------|-----------------|-------------------|

FIRE PIT KIT

| | | | | | | | |
|------------|---|---|---|----|---|---|------|
| 4 X 8 X 8 | - | - | - | 36 | - | - | - |
| 4 X 12 X 8 | - | - | - | 36 | - | - | - |
| TOTAL | - | - | 4 | - | - | - | 1632 |

FIRE PIT KITS INSTALLATION INSTRUCTIONS

- Always use in accordance with all applicable local and state fire codes
- Failure to follow these instructions could result in a hazardous fire causing property damage or physical injury
- Caution: For outdoor use only
- Use the fire ring on stone, dirt or sand surfaces
- For adult use only — do not allow children to use the fire ring
- Do not use on lawns, wooden decks, concrete or asphalt
- Do not use fire ring indoors or under a patio roof
- Do not use in windy conditions
- Do not leave fire unattended at any time
- Do not use under tree branches, trellis, or overhangs of any kind, including covered porches
- Do not use flammable liquids such as gasoline, alcohol, diesel fuel, kerosene, or charcoal lighter fluid to light or relight fires as this may also cause paint to flake off fire ring
- Care should be taken to make sure all combustible material is far enough away from the fire ring not to ignite it
- Avoid using softwoods such as pine or cedar because they are likely to throw sparks — hardwoods are recommended
- Keep children and pets away from the fire ring while it is in use
- Exercise the same precautions you would with any open fire
- Do not wear flammable or loose clothing when tending an open fire
- Avoid touching surfaces as they will be extremely hot
- Assure the fire is completely extinguished before leaving fire ring
- Any modifications to this appliance may be dangerous and are not permitted

ADDITIONAL MATERIALS NEEDED

- Tamper
- Level
- 2 Bags of Leveling Sand
- 2 Tubes of Concrete Adhesive
- Caulk Gun
- 3 Bags of Gravel or Lava Rock
- Shovel
- Optional Marking Paint or Chalk






ACCESSORIES

ACCESSORIES

- 88 Anglia Edger®
- 89 Artforms™
- 91 Granika Step®
- 92 Landings™ Step Unit
- 95 Marina™ Coping



Scan for additional
product information

| RESIDENTIAL | COMMERCIAL | STEPS | CAPS | COPING |
|---|---|---|---|---|
|  |  |  |  |  |
| ✓ | | | | |

SHAPES & SIZES

Multi-Piece



5 1/4 x 7 5/8 x 8



5 1/4 x 10 x 8



5 1/4 x 15 5/8 x 8



5 1/4 x 17 5/8 x 8









| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | UNITS/ LAYER | WEIGHT/ UNIT | WEIGHT/ PALLET |
|------|-----------------|----------------|------------------|------------------|-----------------|-----------------|-------------------|
|------|-----------------|----------------|------------------|------------------|-----------------|-----------------|-------------------|

MULTI-PIECE

| | | | | | | | |
|--------------------|----------|---------|---|----|----|------|------|
| 5 1/4 X 7 5/8 X 8 | 8 LF | 2.67 LF | – | 12 | 4 | 25.7 | 308 |
| 5 1/4 X 10 X 8 | 10 LF | 3.33 LF | – | 12 | 4 | 31 | 372 |
| 5 1/4 X 15 5/8 X 8 | 15.75 LF | 5.25 LF | – | 12 | 4 | 48 | 576 |
| 5 1/4 X 17 5/8 X 8 | 36 LF | 12 LF | – | 24 | 8 | 56 | 1344 |
| TOTAL | 69.75 LF | – | 3 | 60 | 20 | – | 2600 |



Scan for additional product information





| RESIDENTIAL | COMMERCIAL | STEPS | CAPS | FIRE PITS | KITCHEN | FREESTANDING WALL | RETAINING WALL |
|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ | |

SHAPES & SIZES

18 x 36

6 x 36

Installation Hardware



18 x 36 x 3

6 x 36 x 3

Anchor Slide & Nut

Joining Plate

Outer Corner

Inner Corner

Stretcher

50 per box

10 per box

10 per box

10 per box

10 in a bundle





| UNIT | SQFT/PALLET | SQFT/LAYER | LAYER/PALLET | UNITS/PALLET | UNITS/LAYER | SQFT/UNIT | WEIGHT/PALLET |
|------|-------------|------------|--------------|--------------|-------------|-----------|---------------|
|------|-------------|------------|--------------|--------------|-------------|-----------|---------------|

| | | | | | | | |
|---------|------|------|---|-----|---|-----|------|
| 18 x 36 | 81 | 9 | 9 | 18* | 2 | 4.5 | 2638 |
| 6 x 36 | 31.5 | 10.5 | 3 | 21* | 7 | 1.5 | 1029 |

*Total number of both open and closed end panels. 18 x 36 pallets contain 9 of each. 6 x 36 pallets contain 3 open end panels and 18 closed end panels

18 X 36 X 3


6 X 36 X 3



PANEL CONFIGURATIONS


IDEAL:

This configuration uses equal number of panel A and panel B.




NOT OPTIMAL:

This configuration uses panel A only.



NOT RECOMMENDED:






This configuration uses panel B only and the dovetails are exposed. Use ideal configuration as shown above.



*IMPORTANT: When planning configurations, consider the amount of panel A and panel B on a pallet. 18 x 36' panels are sold in pair/layer or in full pallet only. 6 x 36 panels are sold in layer or in full pallet only.



Scan for additional
product information

| RESIDENTIAL | COMMERCIAL | STEPS | CAPS | COPING |
|---|---|---|---|---|
|  |  |  |  |  |
| ✓ | ✓ | ✓ | | |

SHAPES & SIZES

Step Unit



6 x 38 x 16






| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | SQFT/ UNIT | WEIGHT/ UNIT | WEIGHT/ PALLET |
|------------------|-----------------|----------------|------------------|------------------|---------------|-----------------|-------------------|
| STEP UNIT | | | | | | | |
| 6 X 38 X 16 | 25.33 LF | 6.33 LF | 4 | 8 | 3.17 LF | 281.25 | 2250 |

LANDINGS™ STEP UNIT

NATURAL
COLLECTION 




Scan for additional
product information

| RESIDENTIAL | COMMERCIAL | STEPS | CAPS | COPING |
|---|---|---|---|---|
|  |  |  |  |  |
| ✓ | ✓ | ✓ | | |

SHAPES & SIZES

Step Unit



6 x 48 x 18

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | SQFT/ UNIT | WEIGHT/ UNIT | WEIGHT/ PALLET |
|------------------|-----------------|----------------|------------------|------------------|---------------|-----------------|-------------------|
| STEP UNIT | | | | | | | |
| 6 X 48 X 18 | 24 LF | 8 LF | 3 | 6 | 4 LF | 460 | 2760 |




LANDINGS™ STEP UNIT INSTALLATION

Each Landings™ Step Unit is manufactured with two unique face patterns. The step units are palletized and packaged for easy skid-steer loader removal. Care needs to be taken in handling these units. If a blemish occurs on one side of unit, rotate 180° before setting unit into place.


BASE COURSE

Excavate an area 6 inches deep by 1 foot longer by 1 foot wider than the installed step(s) size. Add a minimum of 6 inches of compactable base material, 3/4-inch minus (with fines) aggregate. Compact and level. Set unit and, if desired, add a slight pitch of no more than 1/4 inch toward the front of the step to shed moisture. If installing step units next to a retaining wall, keep units level from front to back.

The Textures on Sides 1 and 2 are Designed to Nest with Minimal Gapping Between the Units.



Place Units so They Nest Tightly Together.



Two unique faces on each step

STAIR TREAD


For each consecutive step, follow base course instructions, making sure the top of the base is even with the top of the previously installed unit. Recommended tread depth is a minimum of 10 inches, but no more than 16 inches. When installing steps adjacent to a finished surface such as pavers, as illustrated, a 6-inch-tall dummy block needs to be installed below the first step.


LANDING

For landing(s) follow base course instructions. Each step unit is manufactured with two unique face patterns. The face patterns are manufactured to nest together, which will create a narrower joint, providing pleasing aesthetics.

STEPS IN A 90-DEGREE WALL

When building into a retaining wall, construct the steps first and build the walls adjacent to the steps.






SKID-STEER LOADER

Slide forks underneath the first step unit and lift off pallet. Set the step unit onto its desired location, using a spacer to ease in fork removal.



A helpful tip to protect the step unit is to wrap the fork of the skid-steer with corrugated plastic packaging from the pallet or other protective materials. Secure to the forks.



CLAMP

Using a materials clamp, center the clamp on the step unit. Attach clamp to skid-steer or mini-excavator and slowly lift the step unit off of the pallet and move it into place. Be sure to have a second person to help guide the unit into place as the machine sets the step unit down.



STRAPS

When using a heavy duty strap(s), start by wrapping the strap(s) around the center if using one or close to step unit ends if two straps are being used. Cinch the strap(s) tight and attach the looped ends of the strap(s) to skid-steer or mini-excavator. Slowly lift the step unit from the pallet and move it into place. Be sure to have a second person to help guide the unit into place as the machine sets the step unit down. Using a spacer will help to ease in the strap removal.



CART

When using a cart, place provided corrugated plastic from pallet or other protective material onto the cart to help protect the step unit. With help from a second person, slowly slide the step unit from the pallet onto the cart. Maneuver the unit carefully into place.

Videos can be found on our YouTube channel:
www.youtube.com/anchorblockmn

MARINA™ COPING




Scan for additional product information

| RESIDENTIAL | COMMERCIAL | STEPS | CAPS | COPING |
|-------------|------------|-------|------|--------|
| | | | | |
| ✓ | | ✓ | ✓ | ✓ |

SHAPES & SIZES


60mm



5¹⁸/₁₆ X 11¹³/₁₆ X 2³/₈

| UNIT | SQFT/ PALLET | SQFT/ LAYER | LAYER/ PALLET | UNITS/ PALLET | SQFT/ UNITS | WEIGHT/ UNIT | WEIGHT/ PALLET |
|--|-----------------|----------------|------------------|------------------|----------------|-----------------|-------------------|
| 60mm | | | | | | | |
| 5 ¹⁸ / ₁₆ X 11 ¹³ / ₁₆ X 2 ³ / ₈ | 97.5 LF | 2.5 LF | 5 | 195 | .5 LF | 18.5 | 3608 |

MARINA COPING - POOL INSTALLATION




MARINA COPING - STEP INSTALLATION

OPTION 1

- A. Marina Coping
- B. Wall Block
- C. Grey block (4 in x 8 in x 16 in) or Wall Block


Note: All elements must be glued together with the concrete adhesive



OPTION 2

- A. Marina Coping
- B. Wall Block

Note: A & B elements must be glued together with the concrete adhesive.



BELGARD® | PAVES THE WAY®

NORTHFIELD EAST
901 E. Troy Ave.
Indianapolis, IN 46203
Ph: 800-424-0190

6045 Dixie Highway,
Bridgeport, MI 48722
Ph: 800-424-0190

5190 Oster Rd.,
Sheffield Village, OH 44054
Ph: 440-949-1167
National Ph: 877-235-4273

STAY CONNECTED WITH BELGARD.



[Pinterest.com/Belgard](https://www.pinterest.com/Belgard)



[Facebook.com/OutdoorLivingbyBelgard](https://www.facebook.com/OutdoorLivingbyBelgard)



[Belgard.com/Blog](https://www.belgard.com/blog)



[YouTube.com/BelgardHardscapes](https://www.youtube.com/BelgardHardscapes)



[Twitter.com/Belgard](https://twitter.com/Belgard)



[Instagram.com/BelgardOutdoorLiving](https://www.instagram.com/BelgardOutdoorLiving)