



**A FASTER & CLEANER WAY
WITH TECHNISEAL'S SYSTEM
FOR PORCELAIN PAVERS**



NextGel PORCELAIN PAVER JOINTING SAND

COLOR	CODE	WEIGHT
White Pearl	141000066	25 lbs
Black Onyx	141000065	25 lbs
Grey Moonstone	141000064	25 lbs
Beige Agate	141000067	25 lbs

CAUTIONS SPECIFIC TO PORCELAIN PAVERS

- Mechanical compaction should be done until joint is saturated. Several passes may be required.
- Porcelain pavers should never be installed with a porcelain to porcelain contact.

(341-444 09/2023)

**NextGel PORCELAIN
PAVER JOINTING SAND**

**A FASTER & CLEANER SOLUTION
FOR GROUTING PORCELAIN PAVERS**



- INNOVATIVE GROUT ALTERNATIVE**
- NO MIXING REQUIRED**
- FAST & EASY**
- COLOR CONSISTENT EFFLORESCENCE-FREE**


Residential & Commercial Use

Convenient 25 lb bag covers 100 sq. ft.

For joints from 1/16" to 1/2"

Contact your local Techniseal® representative, visit techniseal.com or dial 1 800 465-7325 for more details.





**SPECIFICALLY
DESIGNED** for your
PORCELAIN PROJECTS
with **Ultra-Clean Technology**

NextGel™ PORCELAIN PAVER JOINTING SAND



1
**SPREAD
THE SAND**

- Spread product evenly on a small surface. Using the street broom, fill joints completely. Spread sand over short distances.



2
**COMPACT
THE SAND**

- Pass the paver roller compactor over the entire surface to compact the sand.
- Add more product and spread to fill joints again.
- Pass the paver roller compactor over the entire surface a second time.
- **IMPORTANT:** Multiple passes may be required until joint saturation is reached.
- Remove excess sand from the surface with the broom.
- Level the height of the sand with the leaf blower.
- Sand level must be at least 1/8" below top of tiles.




3
**ACTIVATE
BY WATERING**

- Using the water sprayer, starting from bottom of the slope, quickly water the joints of a 100 sq. ft. section* to set the sand (10 to 15 seconds).
- Immediately wet the same section where joints have absorbed more water.
- Check for water accumulation at the surface of the jointing sand as a cue to stop watering. Wait until there is no free water at the surface of the joint and verify the depth of activation.

NECESSARY TOOLS

- Street broom with semi-rigid bristles.
- Paver roller compactor.
- Hand tamper may be needed in restricted areas where using heavier equipment may not be possible.
- Leaf blower.
- Handheld or backpack sprayer for precise watering of the joints.



If NextGel™ PORCELAIN PAVER JOINTING SAND is activated at 75% or more of its depth stop watering. If activated at less than 75%, water for an additional 5 seconds and check again after 30 seconds.


*NextGel™ PORCELAIN PAVER JOINTING SAND is fast to activate. It is very easy to overwater installations with large tiles. Carefully track the watering time during the activation process.



AVAILABLE IN:



**White
Pearl**



**Black
Onyx**



**Grey
Moonstone**



**Beige
Agate**